# S. J. PANDIT, IFS (Retd.) MEMBER SECRETARY SEIAA (GUJARAT)



# STATE LEVEL ENVIRONMENT IMPACT ASSESSMENT AUTHORITY GUJARAT

Government of Gujarat

No. SEIAA/GUJ/EC/4(b)/ 441 /2022

Date:

ByRPAD

1 7 FEB 2022

Time Limit

Sub: Environment Clearance to M/s. Su Mangala Coke Private Limited. for setting up expansion in manufacturing plant of 'Coke oven plants' at Survey no. 274, and 483/P, Lunva, Bhachau, kutch. In Category 4(b) of Schedule annexed with EIA Notification dated 14/09/2006.

Ref: Your Proposal No. SIA/GJ/IND2/62480/2020.

Dear Sir.

This has reference to your application along with EIA report dated 05/04/2021 submitted to SEIAA, seeking Environmental Clearance under Environment Impact Assessment Notification, 2006.

The proposal is for Environmental Clearance to M/s. Su Mangala Coke Private Limited. for setting up expansion in manufacturing plant of 'Coke oven plants' at Survey no. 274, and 483/P, Lunva, Bhachau, kutch. It is an existing unit for manufacturing of metallurgical coke as mentioned below, which falls in the category - 4(b) of the schedule of the EIA Notification-2006:

Sr. No.	Name of the Products	CAS no.	Quantity MT/Month			End-use of the
			Existing	Proposed	Total	products
1	Low Ash metallurgical coke	65996-77-2	2,500	5,000	7,500	Foundries, Blast furnace, Soda Ash Plant

The project activity is covered in 4(b) and is of 'B' Category. Since, the proposed project is located in notified industrial area, public consultation is not required as per paragraph 7(i) (III) (i) (b) of the Environment Impact Assessment Notification-2006.

The SEAC, Gujarat vide their letter dated 01/01/2022 had recommended to the SEIAA, Gujarat, to grant the Environment Clearance for the above-mentioned project based on its meeting held on 25/10/2021. The proposal was considered by SEIAA, Gujarat in its meeting held on 20/01/2022 at Gandhinagar. After careful consideration, the SEIAA hereby accords Environmental Clearance to above project under the provisions of EIA Notification dated 14th September, 2006 subject to the compliance of the following conditions.

#### A.CONDITIONS:

#### A.1SPECIFIC CONDITION:

- Project proponent (PP) shall install CEMS [Continuous Emission Monitoring System] in line to CPCB directions to all SPCB vide letter no. B-29016/04/06PCI-1/5401 dated 05/02/2014 for air emission as per pollutants discharge/emission from respective project and an arrangement shall also be done for reflecting the online monitoring results on the company's server, which can be assessable by the GPCB/CPCB on real time basis. [For Small/Large/Medium (Red Category) & Whichever (Air emission & Effluent discharge) is applicable].
- 2. Entire quantity of coke breeze shall be either recycled or sold to actual end users and records shall be maintained
- The National Ambient Air Quality Emission Standards issued by the Ministry vide G. S. R. No. 826 (E) dated 16th November, 2009 shall be complied with.
- 4. National Emission Standards for Organic Chemicals Manufacturing Industry issued by the Ministry vide G. S. R. 608 (E) dated 21/07/2010 and amended from time to time shall be followed.
  - Unit shall have to adhere to the prevailing area specific policies of GPCB with respect to the discharge of pollutants, and shall carry out the project development in accordance & consistence with the same.
- 6. All measures shall be taken to avoid soil and ground water contamination within premises.

# 7. Safety & Health:

a. PP shall not carry out any activity which attracts PESO permission for the storage and handling of hazardous chemicals.

Office: Gujarat Pollution Control Board, "Paryavaran Bhavan" Sector-10 A, Gandhinagar-382010 Page 1 of 8

Phone No.:- (079) 232-32152,232-41514 Fax No.:- (079) 232-22784 E-mail: msseiaagj@gmail.com. Website:- www.seiaa.gujarat.gov.in

- b. PP shall provide Occupational Health Centre (OHC) as per the provisions under the Gujarat Factories Rule 68-U.
- c. PP shall obtain fire safety certificate / Fire No-Objection certificate (NOC) from the concern authority as per the prevailing Rules / Gujarat Fire Prevention and Life Safety Measures Act, 2016.
- d. Unit shall adopt functional operations/process automation system including emergency response to eliminate risk associated with the hazardous processes.
- e. PP shall carry out mock drill within the premises as per the prevailing guidelines of safety and display proper evacuation plan in the manufacturing area in case of any emergency or accident.
- f. PP shall install adequate fire hydrant system with foam trolley attachment within premises and separate storage of water for the same shall be ensured by PP.
- g. PP shall take all the necessary steps for control of storage hazards within premises ensuring incompatibility of storage raw material and ensure the storage keeping safe distance as per the prevailing guidelines of the concerned authority.
- h. PP shall take all the necessary steps for human safety within premises to ensure that no any harm is caused to any worker/employee or labour within premises.
- i. Flame proof electrical fittings shall be provided in the plant premises, wherever applicable.
- j. Unit shall provide effective fire hydrants, water monitors & foam application system at solvent storage area and unit shall provide adequate safety system such as water sprinklers, water curtains, foam pouring system etc. to restrict cascade fire emergency in solvent storage area.

#### A. 2 WATER:

- 8. Total water requirement for the project shall not exceed 60 KLD. Unit shall reuse 20 KLD of treated effluent within premises. Hence, fresh water requirement shall not exceed 40 KLD and it shall be met through ground water. Prior permission from concerned authority shall be obtained for withdrawal of water.
- 9. The industrial effluent generation from the project shall not exceed 14 KLD.
- 10. Total Industrial effluent shall be treated in ETP and treated effluent shall be recycled back to quenching process. Aaa
- 11. Domestic wastewater generation shall not exceed 7 KL/day for proposed project and it shall be treated in STP. Treated sewage shall be used for gardening.
- 12. Water meter shall be installed and records of daily and monthly consumption shall be maintained.


#### A.3AIR:

13. Unit shall not exceed fuel consumption for D G Set as mentioned below.

Sr. No.	Source of emission With Capacity	Stack Height (meter)	Type of Fuel	Quantity of Fuel MT/Day	Type of emissions i.e. Air Pollutants	Air Pollution Control Measures (APCM)
				Existi	ing	
1	DG Stack (125 KVA) (To be Dismantled)	11	HSD	0.15	PM SO x NOx	Adequate stack height and acoustic enclosure is provided and operated only during power break down.
				Propo	sed	
1	DG Stack (320 KVA)	11	HSD	0.15	PM SO x NOx	Adequate stack height and acoustic enclosure is provided and operated only during power break down.

- 14.
- 15. Unit shall provide adequate APCM with flue gas generation sources to achieve the norms prescribed by GPCB.
- 16. Unit shall provide adequate APCM with process gas generation sources as mentioned below.

Sr. no.	Specific Source of emission (Name of the Product &Process)	Type of emission	Stack/ Vent Height (meter)	Air Pollution Control Measures
1	Coke oven battery (Existing)	PM SO x NOx Hydrocarbon, CO <sub>2</sub>	35	Long masonry tunnel
2	Coke oven battery (Proposed)	PM SO x NOx Hydrocarbon, CO <sub>2</sub>	35	Long masonry tunnel





- that the non recovery coke ovens shall always work under negative pressure.
- 18. Flue gas stack of 35 meter shall be provided to each coke oven batteries (1 existing and 1 proposed).
- Long masonry tunnels shall be provided as APCM as mentioned in process gas matrix to achieve MOEF&CC/CPCB/GPCB norms.
- 20. HSD 150 lit/day shall be used as fuel in D G set (320 KVA) and adequate stack height as per prevailing norms shall be provided.
- 21. The coal shall be transported from Mundra/Kandla port to plant in the tippers / trucks properly covered with tarpaulin sheets tied with rope. Prior to transporting coal from port to plant, moisture content of coal shall be checked and moisture shall be added to pile if it is found below 10 %, in order to prevent fugitive emission during transportation of coal from port to plant
  - a) Movable overhead water sprinkling system with three rotating head sprinkler nozzles shall be provided and used for water sprinkling during receiving/unloading / stacking of coal at Coal Storage Yard. Water shall be sprinkled on coal stock pile periodically to retain some moisture in top layer to reduce the fugitive emission.
  - b) Air borne coal / coke dust shall be controlled with water sprinklers at suitable locations in the plant.
  - c) All Vibrators, Screens, Crushers, Conveyor Belts and conveyor transfer points shall be properly covered.
  - d) Enclosure shall be provided at all loading and unloading operations.
  - e) Regular use of mechanical sweepers shall be practiced. Accumulated dust on the ground and other surfaces, shall be removed / swept regularly and water the area after sweeping.
  - f) Wind barriers shall be provided at suitable places.
  - g) Entire area of operation shall be concreted. Internal roads shall be either concreted or asphalted or paved properly to reduce the fugitive emission during vehicular movement.
- 22. The fugitive emission in the work zone environment shall be monitored. The emission shall conform to the standards prescribed by the concerned authorities from time to time (e.g. Directors of Industrial Safety& Health). Following indicative guidelines shall also be followed to reduce the fugitive emission.
  - Internal roads shall be either concreted or asphalted or paved properly to reduce the fugitive emission during vehicular movement.
  - Air borne dust shall be controlled with water sprinklers at suitable locations in the plant.
  - A green belt shall be developed all around the plant boundary and also along the roads to mitigate fugitive & transport dust emission.
- 23. Regular monitoring of ground level concentration of PM10, PM2.5, SOx, CO2 and NOx shall be carried out in the impact zone and its records shall be maintained. Ambient air quality levels shall not exceed the standards stipulated by the GPCB. If at any stage these levels are found to exceed the prescribed limits, necessary additional control measures shall be taken immediately. The location of the stations and frequency of monitoring shall be decided in consultation with the GPCB.

### A.4 SOLID / HAZARDOUS WASTE:

24. All the hazardous/ solid waste management shall be taken care as mentioned below.

S. No.	Type/Name of Hazardous waste	Specific Source of generation (Name of the Activity, Product etc.)	Category and Schedule as per HW Rules.	Existing (MT/Annum)	Additional (MT/Annum)	Total (MT/Annum)	Management of HW
1	Used oil	Generator set	5.1	0.072	0.078	0.150	Collection, storage and Reuse as lubricant in premises

- 25. Authorized end-users shall have permissions from the concerned authorities under the Rule 9 of the Hazardous and Other Wastes (Management and Transboundary Movement) Rules 2016.
- Unit shall explore the possibilities for environment friendly methods like co-processing of hazardous waste for disposal of Incinerable & land fillable wastes before sending to CHWIF & TSDF sites respectively.
- 27. The project proponent has to obtain membership of TSDF site & CHWIF before obtaining CTO of GPCB. (If applicable)
- 28. Management of fly ash shall be as per the Fly ash Notification 2009 & its amendment time to time and it shall be ensured that there is 100% utilization of fly ash to be generated from the unit.
- 29. STP sludge shall be collected and used as manure in gardening activity or send to TSDF site for landfilling.
- 30. Used oil shall be sold only to the registered re-processors.

#### A. 5OTHER:

31. The project proponent shall carry out the activities (Provision of health checkups at lunva and surrounding Village, Provision of drinking water RO plant in Lunva, Provision of tree guard and transportation of sapling) proposed under CER and it shall be part of the Environment Management Plan (EMP) as per the MoEF&CC's OM no. F. No. 22-65/2017-IA.III

IAA Oud

Office: Gujarat Pollution Control Board, "Paryavaran Bhavan" Sector-10 A, Gandhinagar-382010 Page 3 of 8

Phone No.:- (079) 232-32152 232-41514 Fax No.:- (079) 232-22784

- dated 30.09.2020. This shall be monitored and the monitoring report shall be submitted to the regional office of MoEF&CC as a part of half-yearly compliance report and to the District Collector. The monitoring report shall be posted on the website of the project proponent.
- 32. All the recommendations, mitigation measures, environmental protection measures and safeguards proposed in the EIA report of the project prepared by M/s. Excel Envirotech and submitted by the project proponent and commitments made during presentation before SEAC and proposed in the EIA report shall be strictly adhered to in letter and spirit.

# **B.GENERAL CONDITIONS:**

# **B.1 CONSTRUCTION PHASE:**

- 33. Water demand during construction shall be reduced by use of curing agents, super plasticizers and other best construction practices.
- 34. Project proponent shall ensure that surrounding environment shall not be affected due to construction activity. Construction materials shall be covered during transportation and regular water sprinkling shall be done in vulnerable areas for controlling fugitive emission.
- 35. All required sanitary and hygienic measures shall be provided before starting the construction activities and to be maintained throughout the construction phase.
- 36. First Aid Box shall be made readily available in adequate quantity at all the times.
- 37. The project proponent shall strictly comply with the Building and other Construction Workers' (Regulation of Employment & Conditions of Service) Act 1996 and Gujarat rules made there under and their subsequent amendments. Local bye-laws of concern authority shall be complied in letter and spirit.
- 38. Ambient noise levels shall conform to residential standards both during day and night. Incremental pollution load on the ambient air and noise quality shall be closely monitored during construction phase.
- 39. Use of Diesel Generator (DG) sets during construction phase shall be strictly equipped with acoustic enclosure and shall conform to the EPA Rules for air and noise emission standards.
- 40. Safe disposal of waste water and municipal solid wastes generated during the construction phase shall be ensured.
- 41. All topsoil excavated during construction activity shall be used in horticultural / landscape development within the project site.
- 42. Excavated earth to be generated during the construction phase shall be utilized within the premises to the maximum extent possible and balance quantity of excavated earth shall be disposed off with the approval of the competent authority after taking the necessary precautions for general safety and health aspects. Disposal of the excavated earth during construction phase shall not create adverse effect on neighbouring communities.
- 43. Project proponent shall ensure use of eco-friendly building materials including fly ash bricks, fly ash paver blocks, Ready Mix Concrete [RMC] and lead free paints in the project.
- 44. Fly ash shall be used in construction wherever applicable as per provisions of Fly Ash Notification under the E.P. Act, 1986 and its subsequent amendments from time to time.
- 45. "Wind breaker of appropriate height i.e. 1/3rd of the building height and maximum up to 10 meters shall be provided. Individual building within the project site shall also be provided with barricades.
- 46. "No uncovered vehicles carrying construction material and waste shall be permitted."
- 47. "No loose soil or sand or construction & demolition waste or any other construction material that cause dust shall be left uncovered. Uniform piling and proper storage of sand to avoid fugitive emissions shall be ensured."
- 48. Roads leading to or at construction site must be paved and blacktopped (i.e. metallic roads).
- 49. No excavation of soil shall be carried out without adequate dust mitigation measures in place.
- 50. Dust mitigation measure shall be displayed prominently at the construction site for easy public viewing.
- 51. Grinding and cutting of building materials in open area shall be prohibited.
- 52. Construction material and waste should be stored only within earmarked area and road side storage of construction material and waste shall be prohibited.
- 53. Construction and demolition waste processing and disposal site shall be identified and required dust mitigation measures be notified at the site. (If applicable).

#### **B.2 OPERATION PHASE:**

#### B.2.1 WATER:

- 54. The water meter shall be installed and records of daily and monthly water consumption shall be maintained.
- 55. All efforts shall be made to optimize water consumption by exploring Best Available Technology (BAT). The unit shall continuously strive to reduce, recycle and reuse the treated effluent.

#### B.2.2 AIR:

56. In case of use of spray dryer, the unit shall provide the adequate & efficient APCMs with spray dryer so that there should not be any adverse impact on human health & environment. Unit shall carry out third party monitoring of the proposed Spray dryer & it's APCM through the credible institutes and study report for impacts on Environment and Human Health shall be submitted to GPCB every year along with half yearly compliance report.

- 57. Acoustic enclosure shall be provided to the DG sets (If applicable) to mitigate the noise pollution and shall conform to the EPA Rules for air and noise emission standards.
- 58. Stack/Vents (Whichever is applicable) of adequate height shall be provided as per the prevailing norms for flue gas emission/Process gas emission.
- 59. Flue gas emission & Process gas emission (If any) shall conform to the standards prescribed by the GPCB/CPCB/MoEF&CC. At no time, emission level should go beyond the stipulated standards.
- 60. All the reactors / vessels used in the manufacturing process shall be closed to reduce the fugitive emission.

## B.2.3 HAZARDOUS/SOLID WASTE:

- 61. The company shall strictly comply with the rules and regulations with regards to handling and disposal of Hazardous waste in accordance with the Hazardous and Other Wastes (Management and Transboundary Movement) Rules 2016, as may be amended from time to time. Authorization of the GPCB shall be obtained for collection / treatment / storage / disposal of hazardous wastes.
- 62. Hazardous wastes shall be dried, packed and stored in separate designated hazardous waste storage facility with pucca bottom and leachate collection facility, before its disposal.
- 63. The unit shall obtain necessary permission from the nearby TSDF site and CHWIF. (Whichever is applicable)
- 64. Trucks/Tankers used for transportation of hazardous waste shall be in accordance with the provisions under the Motor Vehicle Act, 1988, and rules made there under.
- 65. The design of the Trucks/tankers shall be such that there is no spillage during transportation
- 66. All possible efforts shall be made for Co-Processing of the Hazardous waste prior to disposal into TSDF/CHWIF
- 67. Management of fly ash (If any) shall be as per the Fly ash Notification 2009 & its amendment time to time and it shall be ensured that there is 100% utilization of fly ash to be generated from the unit.

#### B.2.4 SAFETY:

- 68. The occupier/manager shall strictly comply the provisions under the Factories Act 1948 and the Gujarat Factories Rules 1963
- 69. The project authorities shall strictly comply with the provisions made in Manufacture, Storage and Import of Hazardous Chemicals Rules (MSIHC) 1989, as amended time to time and the Public Liability Insurance Act for handling of hazardous chemicals etc. Necessary approvals from the Chief Controller of Explosives and concerned Govt. Authorities shall be obtained before commissioning of the project. Requisite On-site and Off-site Disaster Management Plans have to be prepared and implemented.
- 70. Main entry and exit shall be separate and clearly marked in the facility.
- 71. Sufficient peripheral open passage shall be kept in the margin area for free movement of fire tender/ emergency vehicle around the premises.
- 72. Storage of flammable chemicals shall be sufficiently away from the production area.
- 73. Sufficient number of fire extinguishers shall be provided near the plant and storage area.
- 74. All necessary precautionary measures shall be taken to avoid any kind of accident during storage and handling of toxic / hazardous chemicals
- 75. All the toxic/hazardous chemicals shall be stored in optimum quantity and all necessary permissions in this regard shall be obtained before commencing the expansion activities.
- 76. The project management shall ensure to comply with all the environment protection measures, risk mitigation measures and safeguards mentioned in the Risk Assessment report.
- 77. Only flame proof electrical fittings shall be provided in the plant premises.
- 78 Storage of hazardous chemicals shall be minimized and it shall be in multiple small capacity tanks / containers instead of one single large capacity tank / containers.
- 79. All the storage tanks shall be fitted with appropriate controls to avoid any leakages. Bund/dyke walls shall be provided for storage tanks for Hazardous Chemicals.
- 80. Handling and charging of the chemicals shall be done in closed manner by pumping or by vacuum transfer so that minimal human exposure occurs.
- 81. Tie up shall be done with nearby health care unit / doctor for seeking immediate medical attention in the case of emergency
- 82. Personal Protective Equipments (PPEs) shall be provided to workers and its usage shall be ensured and supervised.
- 83. First Aid Box and required Antidotes for the chemicals used in the unit shall be made readily available in adequate quantity
- 84. Training shall be imparted to all the workers on safety and health aspects of chemicals handling
- 85. Occupational health surveillance of the workers shall be done and its records shall be maintained. Pre-employment and periodical medical examination for all the workers shall be undertaken as per the Factories Act & Rules.
- 86. Transportation of hazardous chemicals shall be done as per the provisions of the Motor Vehicle Act & Rules.
- 87. The company shall implement all preventive and mitigation measures suggested in the Risk Assessment Report.



Office: Gujarat Pollution Control Board. "Paryavaran Bhavan" Sector-10 A, Gandhinagar-382010 Phone No.:- (079) 232-32152,232-41514 Fax No.:-(079) 232-22784

88. Necessary permissions from various statutory authorities like PESO, Factory Inspectorate and others shall be obtained prior to commissioning of the project.

#### B.2.5 NOISE:

89. The overall noise level in and around the plant area shall be kept well within the standards by providing noise control measures including engineering controls like acoustic insulation hoods, silencers, enclosures etc. on all sources of noise generation. The ambient noise level shall confirm to the standards prescribed under The Environment (Protection) Act, 1986 & Rules.

# B.2.6 CLEANER PRODUCTION AND WASTE MINIMISATION:

- 90. The unit shall undertake the Cleaner Production Assessment study through a reputed institute / organization and shall form a CP team in the company. The recommendations thereof along with the compliance shall be furnished to the GPCB
- 91. The company shall undertake various waste minimization measures such as
  - a. Metering and control of quantities of active ingredients to minimize waste.
  - b. Reuse of by-products from the process as raw materials or as raw materials substitutes
  - c. Use of automated and close filling to minimize spillages.
  - d. Use of close feed system into batch reactors
  - e. Venting equipment through vapour recovery system.
  - f. Use of high pressure hoses for cleaning to reduce wastewater generation.
  - g. Recycling of washes to subsequent batches.
  - h. Recycling of steam condensate.
  - i. Sweeping / mopping of floor instead of floor washing to avoid effluent generation.
  - j. Regular preventive maintenance for avoiding leakage, spillage etc.

# B.2.7 GREEN BELT AND OTHER PLANTATION:

- 92. The unit shall develop green belt within premises as per the CPCB guidelines. However, if the adequate land is not available within the premises, the unit shall take up adequate plantation on road sides and suitable open areas in GIDC estate or any other open areas in consultation with the GIDC / GPCB and submit an action plan of plantation for next three years to the GPCB.
- 93. Drip irrigation / low-volume, low-angle sprinkler system shall be used for the green belt development within the premises.
- 94. The PP shall develop green belt within premises (12776 Sq. m i.e. 33 % of the total plot area) as per the undertaking submitted before SEAC. Green belt shall be developed with native plant species that are significant and used for the pollution abatement as per the CPCB guidelines. It shall be implemented within 3 years of operation phase in consultation with GPCB.

# **B.3 OTHER CONDITION:**

- 95. Project proponent shall install all environment management systems as per the CPCB/GPCB directives regarding the effluent discharge and air emission in working condition.
- 96. Project proponent shall display the copy of Environment Clearance at the site prominently.
- 97. Project proponent shall prepare and follow regular and preventive maintenance plan. The copy of same shall be submitted to SEIAA.
- 98. Project Proponent will have to display the safety procedure in working area.
- 99. The project proponent shall obtain all required permissions for safety, health and fire from competent authorities like PESO/Fire Authority etc. and intimate SEIAA.
- 100. Project Proponent will intimate SEIAA/SEAC/GPCB after obtaining the membership of common facilities like CETP / TSDF / CHWIF / CMEE / Common Spray Dryer as the case may be.
- 101. Extra care will be taken by PP to avoid any accidental blast in boiler, reactor or any machinery in the plant.
- 102. Environment monitoring, training and disaster management plan should be undertaken and complied at regular interval.
- 103. Integrated Regional Office of MoEF&CC, Gandhinagar and GPCB will monitor all environment, safety & health norms as per the prevailing rules.
- 104. Unit shall comply all the applicable standard conditions prescribed in Office Memorandum (OM) published by MoEF&CC vide no. F. No. 22-34/2018-IA.III dated 09/08/2018 for Pharmaceutical and Chemical industries mentioned at (Sr. no. XX).
- 105. The project proponent shall allocate the separate fund for Corporate Environment Responsibility (CER) in accordance to the MoEFCC's Office Memorandum No. F.No.22-65/2017-IA.III dated 01/05/2018 to carry out the activities under CER in affected area around the project. The entire activities proposed under CER shall be monitored and the monitoring report shall be submitted to the regional office of MoEFCC as a part of half-yearly compliance report and to district collector. The monitoring report shall be posted on the website of the project proponent.
- 106. Rain water harvesting of surface as well as rooftop runoff shall be undertaken and the same water shall be used for the various activities of the project to conserve fresh water as well as to recharge ground water. Before recharging the surface run off, pre-treatment must be done to remove suspended matter.
- 107. The unit shall join and participate financially and technically for any common environmental facility / infrastructure as and

- when the same is taken up either by the Industrial Association or GIDC or GPCB or any such authority created for this purpose by the Govt. / GIDC.
- 108. Application of solar energy shall be incorporated for illumination of common areas, lighting for gardens and street lighting in addition the provision for solar water heating system shall also be provided.
- 109. The area earmarked as green area shall be used only for plantation and shall not be altered for any other purpose.
- 110.All the commitments / undertakings given to the SEAC during the appraisal process for the purpose of environmental protection and management shall be strictly adhered to.
- 111 The project proponent shall also comply with any additional condition that may be imposed by the SEAC or the SEIAA or any other competent authority for the purpose for the environmental protection and management.
- 112. In the event of failure of any pollution control system adopted by the unit, the unit shall be safely closed down and shall not be restarted until the desired efficiency of the control equipment has been achieved.
- 113. The project authorities must strictly adhere to the stipulations made by the Gujarat Pollution Control Board (GPCB), State Government and any statutory authority.
- 114 During material transfer there shall be no spillages and garland drain shall be constructed to avoid mixing of accidental spillages with domestic wastewater or storm water.
- 115. Pucca flooring / impervious layer shall be provided in the work areas, chemical storage areas and chemical handling areas to minimize soil contamination.
- 116 Leakages from pipes, pumps shall be minimal and if occurs, shall be arrested promptly.
- 117. No further expansion or modifications in the plant likely to cause environmental impacts shall be carried out without obtaining prior Environment Clearance from the concerned authority.
- 118. The above conditions will be enforced, inter-alia under the provisions of the Water (Prevention & Control of Pollution) Act, 1974, Air (Prevention & Control of Pollution) Act, 1981, the Environment (Protection) Act, 1986, Hazardous Wastes (Management, Handling and Transboundary Movement) Rules, 2008 and the Public Liability Insurance Act, 1991 along with their amendments and rules.
- 119 The project proponent shall comply all the conditions mentioned in "The Companies (Corporate Social Responsibility Policy) Rules, 2014" and its amendments from time to time in a letter and spirit.
- 120. The project management shall ensure that unit complies with all the environment protection measures, risk mitigation measures and safeguards recommended in the EMP report and Risk Assessment study report as well as proposed by project proponent.
- 121 The project authorities shall earmark adequate funds to implement the conditions stipulated by SEIAA as well as GPCB along with the implementation schedule for all the conditions stipulated herein. The funds so provided shall not be diverted for any other purpose.
- 122. The applicant shall inform the public that the project has been accorded environmental clearance by the SEIAA and that the copies of the clearance letter are available with the GPCB and may also be seen at the Website of SEIAA/ SEAC/ GPCB. This shall be advertised within seven days from the date of the clearance letter, in at least two local newspapers that are widely circulated in the region, one of which shall be in the Gujarati language and the other in English. A copy each of the same shall be forwarded to the concerned Regional Office of the Ministry.
- 123.It shall be mandatory for the project management to submit half-yearly compliance report in respect of the stipulated prior environmental clearance terms and conditions in soft copies to the regulatory authority concerned, on 1st June and 1st December of each calendar year.
- 124 Concealing factual data or submission of false/fabricated data and failure to comply with any of the conditions mentioned above may result in withdrawal of this clearance and attract action under the provisions of Environment (Protection) Act, 1986.
- 125. The project authorities shall also adhere to the stipulations made by the Gujarat Pollution Control Board.
- 126 The SEIAA may revoke or suspend the clearance, if implementation of any of the above conditions is not found satisfactory
- 127 The company in a time bound manner shall implement these conditions. The SEIAA reserves the right to stipulate additional conditions, if the same is found necessary.
- 128. The project authorities shall inform the GPCB, Regional Office of MoEF and SEIAA about the date of financial closure and final approval of the project by the concerned authorities and the date of start of the project.
- 129. This environmental clearance is valid for seven years from the date of issue
- 130 Any appeal against this environmental clearance shall lie with the National Green Tribunal, if preferred, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.
- 131. Submission of any false or misleading information or data which is material to screening or scoping or appraisal or decision on the application makes this environment clearance cancelled.

# B.4 COMPLIANCE OF ENVIRONMENT CLEARANCE/REPORTING/ADMINISTRATION/APPEAL:

132 Project proponent shall inform to all the concerned authorities including Municipal Corporation and District Collector and



Office: Gujarat Pollution Control Board, "Paryavaran Bhavan" Sector-10 A, Gandhinagar-382010 Page 7 of 8
Phone No.:- (079) 232-32152,232-41514 Fax No.:- (079) 232-22784

E-mail: msseiaagj@gmail.com, Website:- www.seiaa.gujarat.gov.in

- shall also give wide publicity through advertisement in minimum two local newspapers within seven days, about the Environment Clearance order accorded.
- 133. Project proponent shall appoint a key person in the organization who shall be responsible for compliance of above condition fully on behalf of the proponent. It will not mean that appointing a key person will exempt the project proponent from the responsibility of compliance. Any change in key person shall immediately be informed to SEIAA and all concerned authorities.
- 134. Designated key person shall submit six monthly compliance report to SEIAA/SEAC, MOEF&CC, GPCB and Nodal Department of the Government.
- 135. The Nodal Department or any authority or officer authorized by MOEF&CC/SEIAA can inspect the site of the project and all the facilities, for verification of compliances of environment clearance conditions.
- 136.In case of violation reported upon, the project proponent shall be responsible for all the legal actions as per Environment Protection Act, 1986 including SEIAA may cancel, withdraw or keep in abeyance, the Environment Clearance accorded.
- 137. Any person including the project proponent affected by this Environment Clearance order may file appeal to Honorable National Green Tribunal West Zone branch, Pune, preferably within a period of thirty days from the date of issue of Environment Clearance as prescribe under section 16 of National Green Tribunal Act 2010.
- 138.All complains and public grievance or representations may be addressed to SEIAA/SEAC in the email addresses (a) msseiaagj@gmail.com& (b) seacgujarat@gmail.com

With regards. Yours sincerely,

ed-

(S. J. PANDIT) Member Secretary

Issued to: M/s. Su Mangala Coke Private Limited. Survey no. 274, and 483/P. Lunva, Bhachau, kutch

## Copy to:-

- The Secretary, SEAC, C/O. G.P.C.B. Gandhinagar 382010.
- The Additional Chief Secretary, Forests & Environment Department, Govt. of Gujarat, Block 14, 8th floor, Sachivalaya, Gandhinagar-382010.
- The Chairman, Central Pollution Control Board, Parivesh Bhavan, CBD -cum-Office Complex, East Arjun Nagar, New Delhi-110032
- 4. Scientist C, Integrated Regional Office, Ministry of Environment and Forests, Aranya Bhavan, Sector-10, Gandhinagar -382010
- Monitoring Cell, Ministry of Environment and Forests, Paryavaran Bhavan, CGO Complex, New Delhi-110003.
- 6. The Member Secretary, Gujarat Pollution Control Board, Paryavaran Bhavan, Sector-10 A, Gandhinagar-382010
- 7. Select File

(S. J. PANDIT) Member Secretary